



## UK-3000

### Industrial Flooring System

#### DESCRIPTION

UK-3000 defines versatility by wrapping four products into one.

- (1) Topcoat, Sealer, Primer
- (2) Self-Leveling Resurfacer
- (3) High Build, Standard Duty Overlay
- (4) High Build, Severe Duty Overlay

Ready for foot traffic in 2-10 hours.

#### RECOMMENDED USES

- ✓ Bakeries
- ✓ Pulp & Paper Mills
- ✓ Freezers & Coolers
- ✓ Food Processing Facilities



# UK-3000

## Industrial Flooring System

# Absolute Protective Coatings

### PERFORMANCE DATA

#### Traffic Ready

2-10 hours

#### Flexural Strength

1885, psi

#### Compressive Strength

7370, psi

#### Tensile Strength

860, psi

#### Mixing Ratio

1:1, fillers create a third component

#### Coverage

UT-4 - 6.25 sq ft/gal @ 250 mils  
USL-3 - 6.25 sq ft/gal @ 250 mils  
USL-3 -12.5 sq ft/gal @ 125 mils  
US-3 - 100 sq ft/gal @ 15 mils

#### Colors

All Standard Colors

#### Packaging

8 gallon kit (resins)  
US-3 Filler, 40 lb bag  
USL-3 Filler, 60 lb bag  
UT-4 Filler, 50 lb bag



### PRODUCT OVERVIEW

UK-3000 urethane overlay system available in sealer, self-leveling slurry, and trowel grades. Designed for the toughest environments and perfect for those demanding industrial, food processing, and commercial kitchen applications.

- ✓ No Odor
- ✓ Bonds without primer (most applications)
- ✓ Withstands Thermal Shock
- ✓ Fast Cure - Traffic ready in 2 - 10 hours
- ✓ Non-flammable, no peroxides or heavy metals
- ✓ Impact and Chemically Resistant
- ✓ VOC Compliant

### TYPICAL USAGE AND APPLICATIONS

UK-3000 is the most versatile, multipurpose industrial coating system available today. Whether thin mil topcoat/sealer application or for high build/severe duty situations.

UK-3000 delivers substantial value on the price/performance equation. UK-3000 consists of a base resin system combined with one of 4 possible filler systems to handle light foot traffic to heavy forklift traffic, chemical attack, thermal shock, and high impact to high wear.

- ✓ Thin-Build Sealer, Topcoat, and Primer
- ✓ Medium Build Self-Leveling Slurry Resurfacer
- ✓ High Build and Severe Duty Overlay

For a demonstration of UK-3000 in your area, please call us at 360-673-6404 or send a note to [absoluteconcretecolors@gmail.com](mailto:absoluteconcretecolors@gmail.com)

### RECOMMENDED READING

MSDS [Material Safety] Product Data Sheet

Available online at [www.absoluteconcretecolors.net](http://www.absoluteconcretecolors.net)

Recommendations for product use based on tests believed to be reliable. Field conditions vary widely. For this reason, the user must determine product suitability for the particular use and specific applications. Absolute Concrete Colors assumes no liability for injury, loss or damage resulting from use of this product. This product is not intended for retail distribution and should only be used by construction professionals experienced in the application and handling of potentially hazardous chemical compounds.